

**\*\*PRECAST WALLS AVAILABLE 6" OR 8"\*\***

**Product Specification:**

Concrete = 4000 PSI At 28 Days  
Type II Cement

Reinforcement Steel Grade 60:  
Structure Piece Rein: Per plan specifications  
or ASTM-C478

**Structure Weight:**

Cone = (6" Walls) 5,217 LBS. 2.61 Tons  
(8" Walls) 5,867 LBS. 2.93 Tons

Wall = (6" Walls) 1,253 LBS./V.Ft.  
(8" Walls) 1,721 LBS./V.Ft.

Bottom Slab = (6" Walls) 3,061 LBS., 1.53 Tons  
(8" Walls) 3,391 LBS., 1.70 Tons

Bottom Slab Is Cast W/ Waterstop. Walls Are Cast As A Secondary Pour.

Coatings & Liners =See Sanitary Sewer  
General Notes

Joint Sealant =See Sanitary Sewer  
General Notes



**U.S. FOUNDRY & MFG. CORP. RING & COVERS** \*Or Approved Equal\*

U.S.F. NO.	Clear Opening	Load Rating	Total Weight
170 E	22 1/2"	Heavy Duty	280
310 A	20 3/4"	Heavy Duty	530
420 C	20 5/8"	Heavy Duty	405

O-Ring Available For All Rings As Listed Above.  
See U.S. Foundry Catalog For Other Rings & Covers.

**Florida Plant Locations**

**Orlando**

690 W. Taft-Vineland Rd., Orlando, Fl. 32824  
Phone: 407-855-7580 Fax: 407-768-8428

**Jacksonville**

5995 Soutel Drive, Jacksonville, Fl 32219  
Phone: 904-768-7081 Fax: 904-768-8428

**Brooks Products-Medley**


7311 N.W 77th Street, Medley, Fl 33166  
Phone: 305-887-3527 Fax: 305-887-7119

**Marianna**

4043 Family Dollar Parkway, Marianna, Fl 32448  
Phone: 850-482-5830 Fax 866-850-9049

**Cape Coral**

2140 Pondella Rd, Cape Coral, Fl. 33903  
Phone: 239-574-8896 Fax: 239-574-9517



**5DH-MH**

**5' Dia Doghouse Manhole  
w/ Concentric Cone**

www.oldcastleprecast.com

Copyright © 2003 Oldcastle Precast, Inc.